



BE SURE. BUILD SURE.

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name Donnitil Oil Ex

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Oil stain remover

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name Donnitol Oil Ex

(Contd. of page 1)

Hazard pictograms



GHS02 GHS05 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

Reaction mass of ethylbenzene and xylene
Isotridecanol, ethoxylated (5-6 EO)

Hazard statements

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components.

Dangerous components:

EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	80-100%
-----------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name **Donnitil Oil Ex**

(Contd. of page 2)

CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<10%
CAS: 9043-30-5	Isotridecanol, ethoxylated (5-6 EO) Eye Dam. 1, H318; Aquatic Chronic 3, H412	≥3-<5%
CAS: 1022990-65-3	Oxirane, 2-ethyl-, polymer with oxirane, mono-C11-15-sec-alkyl ethers Acute Tox. 4, H302; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	≥2.5-<5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing** Do not induce vomiting; instantly call for medical help.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents** Water.
Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name **Donnitil Oil Ex**

(Contd. of page 3)

- **6.2 Environmental precautions:** Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 3

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Components with critical values that require monitoring at the workplace:**

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

· **DNELs**

Reaction mass of ethylbenzene and xylene

Oral DNEL 1.6 mg/kg bw/Tag (ArL)

mg/kg bw/Tag (Workers)

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name Donnitil Oil Ex

(Contd. of page 4)

Dermal	DNEL	180 mg/kg bw/day (ArL)
Inhalative	DNEL	211 mg/m ³ (ArL)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Dermal	DNEL	153.5 mg/kg bw/day (ArL)
Inhalative	DNEL	275 mg/m ³ (ArL)

· PNECs

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

PNEC	0.635 mg/l (Fresh water)
	100 mg/l (K1a)
	0.0635 mg/l (Mew)
PNEC	0.29 mg/kg dwt (Bod)
	0.329 mg/kg dwt (Marine water sediment)
	3.29 mg/kg dwt (Fresh water sediment)

· CAS No. Designation of material % Type Value Unit

· Additional Occupational Exposure Limit Values for possible hazards during processing:

CAS: 1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

CAS: 100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
	Sk

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution or when application is performed at confined area with adequate mechanical ventilation meeting local authority requirements, use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
Filter AX.

· Hand protection

Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name Donnitil Oil Ex

(Contd. of page 5)

- **Material of gloves** *The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Fluorocarbon rubber (Viton)
Recommended thickness of the material: ≥ 0.4 mm*
- **Penetration time of glove material** *The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.
Breakthrough time: $> = 480$ min*
- **Eye/face protection** *Not required.*
- **Body protection:** *Protective work clothing.*

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** *Colourless*
- **Smell:** *Characteristic*
- **Melting point/freezing point:** *Not determined*
- **Boiling point or initial boiling point and boiling range** *137 °C*
- **Lower and upper explosion limit**
- **Lower:** *1.1 Vol %*
- **Upper:** *7 Vol %*
- **Flash point:** *25 °C*
- **Auto-ignition temperature:** *500 °C*
- **pH** *Not applicable.
Not determined.*
- **Viscosity:**
- **Kinematic viscosity** *Not determined.*
- **dynamic:** *Not determined.*
- **Solubility**
- **Water:** *Not miscible or difficult to mix*
- **Steam pressure at 20 °C:** *5 hPa*
- **Density and/or relative density**
- **Density at 20 °C** *0.89 g/cm³*
- **9.2 Other information**
- **Appearance:**
- **Form:** *Fluid*
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** *Product is not selfigniting.*

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name **Donnitil Oil Ex**

(Contd. of page 6)

· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	
· Acute toxicity	Harmful in contact with skin. Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523-4000 mg/kg (rat)
------	------	-----------------------

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name Donnitol Oil Ex

(Contd. of page 7)

Dermal	LD50	1100 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)
CAS: 108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8500 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
CAS: 9043-30-5 Isotridecanol, ethoxylated (5-6 EO)		
Oral	LD50	>2000 mg/kg (rat)
	NOAEL	>50 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 1022990-65-3 Oxirane, 2-ethyl-, polymer with oxirane, mono-C11-15-sec-alkyl ethers		
Oral	LD50	2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

Reaction mass of ethylbenzene and xylene

EC50/72h	2.2 mg/l (Selenastrum capricornutum)
LC50/96h	2.6 mg/l (Oncorhynchus mykiss)
NOEC	16 mg/l (BEL)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

LC50/96h	134 mg/l (Oncorhynchus mykiss)
	161 mg/l (Pimephales promelas)
EC50	>1000 mg/l (BEL)
EC50/48h	>500 mg/l (Daphnia magna)
NOEC	47.5 mg/l (Ory)
EC50/3d	>1000 mg/l (Selenastrum capricornutum)

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name Donnitil Oil Ex

(Contd. of page 8)

CAS: 9043-30-5 Isotridecanol, ethoxylated (5-6 EO)

EC50/72h	1-10 mg/l (Desmodesmus subspicatus)
LC50/96h	1-10 mg/l (Cyp)
EC50/48h	1-10 mg/l (Daphnia magna)
NOEC	1.36 mg/l (Daphnia magna)
	1.73 mg/l (fish)
EC10/3d	0.6 mg/l (algae)

CAS: 1022990-65-3 Oxirane, 2-ethyl-, polymer with oxirane, mono-C11-15-sec-alkyl ethers

EC50/48h	4.22 mg/l (Daphnia magna)
ErC50/72h	1.25 mg/l (Desmodesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR, IMDG, IATA** PAINT RELATED MATERIAL

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name **Donnitil Oil Ex**

(Contd. of page 9)

· 14.3 Transport hazard class(es)	
· ADR	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	
· Kemler Number:	Warning: Flammable liquids. 30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	
Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name *Donnitil Oil Ex*

(Contd. of page 10)

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

**· Qualifying quantity (tonnes)
for the application of lower-
tier requirements** 5000 t

**· Qualifying quantity (tonnes)
for the application of upper-
tier requirements** 50000 t

**· 15.2 Chemical safety
assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases
*H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.*

**· Department issuing data
specification sheet:** *Environment protection department.*

· Abbreviations and acronyms: *RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)*

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024

Version number 36 (replaces version 35)

Revision: 06.05.2024

Trade name Donnitil Oil Ex

(Contd. of page 11)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB