

Page 1/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name MC-Estripox - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Epoxy coating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400

Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.

Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS07 GHS08 GHS09



Page 2/13

Safety data sheet according to UK REACH

Revision: 14.07.2024 Printing date 14.07.2024 Version number 26 (replaces version 25)

Trade name MC-Estripox - Komponente A

(Contd. of page 1)

· Signal word

Danger

Hazard-determining

components of labelling:

epoxide derivates crystalline silica Alkyl Glycidyl Ether maleic anhydride

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H360F May damage fertility.

H372 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation. H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/

attention.

P405 Store locked up.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

Dangerous components:		
	epoxide derivates	30-60%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	
CAS: 14808-60-7	crystalline silica STOT RE 1, H372	10-30%
CAS: 68609-97-2	Alkyl Glycidyl Ether	≥1-<5%
	Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	1

(Contd. on page 3)



Page 3/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

Trade name MC-Estripox - Komponente A

		(Contd. of page 2)
CAS: 100-51-6	Benzyl alcohol	<2.5%
	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 222417-26-7	Polyacrylate	≥0.025-<0.25%
	Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	
CAS: 108-31-6	maleic anhydride	<0.001%
EINECS: 203-571-6	Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	
· Additional informa	tion For the wording of the listed hazard phrases refer	to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

GB



Page 4/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

Trade name MC-Estripox - Komponente A

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy

resins.

Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions:

Keep container tightly closed in a well-ventilated place.

Storage class 6.1C

GB



Page 5/13

Safety data sheet according to UK REACH

Revision: 14.07.2024 Printing date 14.07.2024 Version number 26 (replaces version 25)

Trade name MC-Estripox - Komponente A

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 108-31-6 maleic anhydride

WEL | Short-term value: 3 mg/m³

Long-term value: 1 mg/m³

Sen

· DNELs

Oral

CAS: 68609-97-2 Alkyl Glycidyl Ether

DNEL 0.75 mg/kg bw/day (ArL)

Inhalative DNEL 0.49 mg/m³ (ArL)

CAS: 100-51-6 Benzyl alcohol

DNEL 4 mg/kg bw/Tag (ArL)

20 mg/kg bw/Tag (Ark)

Dermal DNEL 8 mg/kg bw/day (ArL)

40 mg/kg bw/day (Ark)

Inhalative DNEL 22 mg/m³ (ArL)

110 mg/m3 (Ark)

PNECs

CAS: 68609-97-2 Alkyl Glycidyl Ether

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

CAS: 100-51-6 Benzyl alcohol

PNEC 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

Additional information:

The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering

controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

Keep away from food, drink and animal feed. hygienic measures

> Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

(Contd. on page 6)



Page 6/13

Safety data sheet according to UK REACH

Version number 26 (replaces version 25) Revision: 14.07.2024 Printing date 14.07.2024

Trade name MC-Estripox - Komponente A

(Contd. of page 5)

Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/ white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Hand protection

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves

You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min

· Eye/face protection

Tight-fitting safety goggles. Safety goggles.

Body protection:

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.



Page 7/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

Trade name MC-Estripox - Komponente A

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: According to product specification

Smell: CharacteristicMelting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range >320 °C (CAS: 1675-54-3 epoxide derivates)

· Flash point: >61 °C

• Auto-ignition temperature: 455 °C (CAS: 1675-54-3 epoxide derivates)

pH Not determined.

Viscosity:

• Kinematic viscosity Not determined. • dynamic at 20 °C: 18000 mPas

Solubility

· Water: Not miscible or difficult to mix

• Steam pressure at 20 °C: 0 hPa (CAS: 1675-54-3 epoxide derivates)

· Density and/or relative density

Density at 20 °C 1.69 g/cm³

· 9.2 Other information

· Appearance:

· Form: Viscous

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void Void · Aerosols Void Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals

(Contd. on page 8)



Page 8/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

Trade name MC-Estripox - Komponente A

(Contd. of page 7)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	LD/LC50 values that are relevant for classification:		
CAS: 167	CAS: 1675-54-3 epoxide derivates		
Dermal	LD50	23000 mg/kg (rabbit)	
CAS: 686	CAS: 68609-97-2 Alkyl Glycidyl Ether		
Oral	LD50	17100 mg/kg (rat)	
CAS: 100	CAS: 100-51-6 Benzyl alcohol		
Oral	LD50	1230 mg/kg (rat)	
	NOAEL 2nd year study	200 mg/kg (mouse)	
		200 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>4178 mg/l (rat)	
CAS: 108	CAS: 108-31-6 maleic anhydride		
Oral	LD50	1090 mg/kg (rat)	
Dermal	LD50	2620 mg/kg (rat)	

Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

• Germ cell mutagenicity
• Carcinogenicity
• Carcinogenicity
• Based on available data, the classification criteria are not met.
• Based on available data, the classification criteria are not met.

Reproductive toxicity May damage fertility.

STOT-single exposure
Based on available data, the classification criteria are not met.
Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

(Contd. on page 9)



Page 9/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

Trade name MC-Estripox - Komponente A

(Contd. of page 8)

· Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties		
CAS: 128-37-0	2,6-Di-tert-butyl-p-cresol	List II
CAS: 556-67-2	Octamethylcyclotetrasiloxane	List II; III

SECTION 12: Ecological information

· 12.1 Toxicity

· 12.1 TOXICE · Aquatic tox	•
CAS: 1675-54-3 epoxide derivates	
IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
CAS: 68609	9-97-2 Alkyl Glycidyl Ether
EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)
	1800 mg/l (Lepomis macrochirus)
EC50	>100 mg/l (BEL)
NOEC	500 mg/l (Pseudokirchneriella subcapitata)
CAS: 100-5	1-6 Benzyl alcohol
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

10 mg/l (Lepomis macrochirus)

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

- GB



Page 10/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

Trade name MC-Estripox - Komponente A

(Contd. of page 9)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDO
IMDG	SUBSTANCE, LIQUID, N.O.S. (epoxide derivate ENVIRONMENTALLY HAZARDO
IIIIDG	SUBSTANCE, LIQUID, N.O.S. (epoxide derive
	Alkylbenzene), MARINÉ POLLUTANT
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances articles.
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	Α

(Contd. on page 11)



Page 11/13

Safety data sheet according to UK REACH

Printing date 14.07.2024 Version number 26 (replaces version 25) Revision: 14.07.2024

Trade name MC-Estripox - Komponente A

	(Contd. of page 1
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml -
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
•	SUBSTANCE, LIQUID, N.O.S. (EPOXID
	DERIVATES), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

(Contd. on page 12)



Page 12/13

Safety data sheet according to UK REACH

Version number 26 (replaces version 25) Revision: 14.07.2024 Printing date 14.07.2024

Trade name MC-Estripox - Komponente A

(Contd. of page 11)

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H360F May damage fertility.

H372 Causes damage to organs through prolonged or repeated

exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. H411

EUH071 Corrosive to the respiratory tract.

EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 13)



Page 13/13

Safety data sheet according to UK REACH

Printing date 14.07.2024

Version number 26 (replaces version 25)

Trade name MC-Estripox - Komponente A

(Contd. of page 12)

Revision: 14.07.2024

Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 1B: Reproductive toxicity - Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard –

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

* * Data compared to the previous version altered.

GB