

Page 1/13

Safety data sheet

according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Trade name 1.2 Relevant identified uses of the substance or mixture	<u>MC-Estripox - Komponente A</u>
and uses advised against · Application of the substance / the mixture	No further relevant information available. Epoxy coating
• 1.3 Details of the supplier of the supplier of the supplier:	he safety data sheet MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
 Informing department: 1.4 Emergency telephone number: 	msds@mc-bauchemie.de Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

		o ()
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 1B	H360F	May damage fertility.
STOT RE 1	H372	Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
Aquatia Chrania 2	L111	Taxia to aquatia life with long locing official

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



(Contd. on page 2)

GB



Page 2/13

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

Trade name MC-Estripox - Komponente A

		(Contd. of page 1)
· Signal word	Danger	
· Hazard-determining		
components of labelling:	4,4'-Methylened	iphenyldiglycidyl ether
	Quartz sand	
		(C12-14-alkyloxy)methyl)derivatives
	Maleic anhydride	
 Hazard statements 	H315 Causes s	
		serious eye irritation.
		se an allergic skin reaction.
	H360F May dam	
		damage to the lung through prolonged or repeated
		e. Route of exposure: Inhalation.
_		aquatic life with long lasting effects.
Precautionary statements	P260	Do not breathe dust/fume/gas/mist/vapours/
	D004	spray.
	P261	Avoid breathing dust/fume/gas/mist/vapours/
	P273	spray. Avoid release to the environment.
	P273 P280	
	F200	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for
	1 303 11 301 11 30	several minutes. Remove contact lenses, if
		present and easy to do. Continue rinsing.
	P405	Store locked up.
· Additional information:		ns epoxy constituents. May produce an allergic
	reaction	
[.] 2.3 Other hazards		
[•] Results of PBT and vPvB as	sessment	
· PBT:	Not applicable.	
·vPvR·	Not applicable	

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:
- Mixture consisting of the following components.

CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether	30-60%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 14808-60-7	Quartz sand	10-30%
EINECS: 238-878-4	STOT RE 1, H372	
CAS: 68609-97-2	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives	≥1-<5%
EINECS: 271-846-8	Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 100-51-6	Benzyl alcohol	<1.5%
EINECS: 202-859-9	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	



Page 3/13

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

Trade name MC-Estripox - Komponente A

	(Co	ntd. of page 2)
CAS: 71302-83-5	Hydrocarbons, C9-unsaturated, polymerised	≥1-<1.5%
	Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	
CAS: 108-31-6	Maleic anhydride	<0.001%
EINECS: 203-571-6 Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071		
	Specific concentration limit: Skin Sens. 1A; H317: $C \ge 0.001$ %	
• Additional information For the wording of the listed hazard phrases refer to sec		ction 16.

SECTION 4: First aid measures				
• 4.1 Description of first aid	d measures			
General information	Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.			
· After inhalation	Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.			
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.			
· After eye contact	Rinse opened eye for several minutes under running water. Call a doctor immediately			
· After swallowing	Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.			
 4.2 Most important sympt and effects, both acute at 	toms			
delayed	Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.			

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture · 5.3 Advice for firefighters

· Protective equipment:

No special measures required.

No further relevant information available.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures 6.2 Environmental precautions:

Not required.

Prevent material from reaching sewage system, holes and cellars. (Contd. on page 4)

GB



Page 4/13

Safety data sheet according to UK REACH

Printing date 15.04.2025Version number 36 (replaces version 35)Revision: 15.04.2025

Trade name MC-Estripox - Komponente A

0.0 Mathematics and mark	(Contd. of page 3)
6.3 Methods and mate containment and clea	erial for aning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
6.4 Reference to othe	
sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment.
	See Section 13 for information on disposal.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling	Open and handle containers with care. Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided. Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
 Information about protection against explosions and fires: 	Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
 7.2 Conditions for safe storag Storage Requirements to be met by 	e, including any incompatibilities
storerooms and containers: Further information about	No special requirements.
storage conditions: • Storage class	<i>Keep container tightly closed in a well-ventilated place.</i> 6.1C

SECTION 8: Exposure controls/personal protection

· 8.1	Control	parameters
-------	---------	------------

· Components with critical values that require monitoring at the workplace:

CAS: 108-31-6 Maleic anhydride

WEL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen

(Contd. on page 5)



Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

Page 5/13

Trade name MC-Estripox - Komponente A

			Contd. of page	
DNELS	00-07-2	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives		
Dermal		0.75 mg/kg bw/day (ArL)		
		0.49 mg/m ³ (ArL)		
		enzyl alcohol		
Oral		4 mg/kg bw/Tag (ArL)		
0.0	2=	20 mg/kg bw/Tag (Ark)		
Dermal	DNFI	8 mg/kg bw/day (ArL)		
		40 mg/kg bw/day (Ark)		
Inhalative	DNEL	22 mg/m ³ (ArL)		
	2==	110 mg/m ³ (Ark)		
PNECs				
	00 07 1	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives		
PNEC 0.0				
		g/l (Freshwater)		
	-	'kg dwt (Bod) 'kg dwt (Sediment)		
	-			
	-	kg dwt (Fresh water sediment)		
		enzyl alcohol I (Marine water sediment)		
	-			
	1 mg/l (l			
		esh water sediment) //a dut (Rod)		
	-	'kg dwt (Bod) g dwt (Fresh water sediment)		
Additiona	-	,	used as has	
		C 1	seu as vas	
8.2 Expos				
Appropria controls	ale eng	No further data; see section 7.		
	l prote	ction measures, such as personal protective equipment		
General p				
hygienic	measu			
		Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.		
		Avoid contact with eyes and skin.		
Breathing	g equip		by ventilati	
-		measures or if rooms cannot be technically ventilate	d, respirato	
		protection must be worn: Use combination filter A	1-P2 (brow	
		white) in rooms that cannot be ventilated. If oxygen		
		expected, use self-contained breathing apparat wearing time limits according to §9 (3) GefStoffV ii		
		weating time mints according to §9 (5) Gerston v in with BGR 190.	, sonjunioli	
Hand pro	tection	Selection of the glove material on consideration of th	e penetrati	
		times, rates of diffusion and the degradation	land on no	
			Contd. on page	

⁻ GB



Safety data sheet according to UK REACH

Printing date 15.04.2025

Trade name MC-Estripox - Komponente A

Version number 36 (replaces version 35)

Revision: 15.04.2025

(Contd. of page 5)

Page 6/13

Material of gloves You can find help with choosing gloves on the website https:// www.bgbau.de/fileadmin/Gisbau/Projekte.pdf For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. Nitrile rubber

Recommended material thickness > 0.4 mm

	Recommended material thickness. 2 0.4 mm
· Penetration time of glove	
material	The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
	The following applies to all other gloves:
	The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
	Nitrile rubber
	Material thickness: \geq 0.40 mm
	Penetration time: \geq 480 min
	Butyl rubber:
	Material thickness: \geq 0.5 mm
	Penetration time: \geq 480 min
· Eye/face protection	Tight-fitting safety goggles.
, , , , , , , , , , , , , , , , , , ,	Safety goggles.
· Body protection:	Protective clothing
	Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the
	lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chen General Information 	
· Colour:	According to product specification
· Smell:	Characteristic
 Melting point/freezing point: 	Not determined
· Boiling point or initial boiling point and	
boiling range	>320 °C (CAS: 1675-54-3 4,4'-
	Methylenediphenyldiglycidyl ether)
	(Contd. on page 7)



Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

Page 7/13

Trade name MC-Estripox - Komponente A

	(Contd. of page 6
Flash point: Auto-ignition temperature: pH	>61 °C 455 °C (CAS: 1675-54-3 4,4'- Methylenediphenyldiglycidyl ether) Not determined.
⁻ рп · Viscosity:	Not determined.
Viscosity. Kinematic viscosity	Not determined.
dynamic at 20 °C:	18000 mPas
Solubility	10000 //// 43
· Water:	Not miscible or difficult to mix
Steam pressure at 20 °C:	0 h P a (CAS: 1675-54-3 4,4'- Methylenediphenyldiglycidyl ether)
 Density and/or relative density 	
Density at 20 °C	1.69 g/cm³
9.2 Other information	
Appearance:	
Form:	Viscous
Important information on protection of hea	alth
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Information with regard to physical haz	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

(Contd. on page 8)



Page 8/13

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

Trade name MC-Estripox - Komponente A

· 10.2 Chemical stability	(Contd. of page 7)
• Thermal decomposition /	
conditions to be avoided:	No decomposition if used according to specifications.
 10.3 Possibility of hazardous 	
reactions	No dangerous reactions known
 10.4 Conditions to avoid 	No further relevant information available.
• 10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous	
decomposition products:	No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met. · Acute toxicity

CAS: 167	5-54-3 4,4'-Methylened	liphenyldiglycidyl ether
Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	23000 mg/kg (rabbit)
		>2000 mg/kg (rat)
CAS: 686	09-97-2 Oxirane, mon	o((C12-14-alkyloxy)methyl)derivatives
Oral	LD50	17100 mg/kg (rat)
CAS: 100-	-51-6 Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	y 200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
CAS: 108	-31-6 Maleic anhydrid	e
Oral	LD50	1090 mg/kg (rat)
Dermal	LD50	2620 mg/kg (rat)
Skin corre Serious e		Causes skin irritation. Causes serious eye irritation.
sensitisat		May cause an allergic skin reaction.
		Based on available data, the classification criteria are not met.
Carcinog		Based on available data, the classification criteria are not met.
		May damage fertility. Record on survivolution data, the eleccification criteria are not mat
	eated exposure	Based on available data, the classification criteria are not met. Causes damage to the lung through prolonged or repeate exposure. Route of exposure: Inhalation.
Aspiratio		Based on available data, the classification criteria are not met. (Contd. on page



Printing date 15.04.2025

Safety data sheet according to UK REACH

Version number 36 (replaces version 35)

Revision: 15.04.2025

Trade name MC-Estripox - Komponente A

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

CAS: 556-67-2 Octamethylcyclotetrasiloxane

SECTION 12: Ecological information

· 12.1 Toxici	ty		
· Aquatic to	kicity:		
CAS: 1675-	-54-3 4,4'-Methylen	ediphenyldiglycidyl ether	
LC50/72h	>11 mg/l (algae)		
IC50	>42.6 mg/l (Bak)		
LC50/96h	2 mg/l (Oncorhynchus mykiss)		
	1.3 mg/l (fish)		
EC50/48h	2.1 mg/l (daphnia)		
	1.8 mg/l (Daphnia I	magna)	
ErC50/72h	11 mg/l (Selenastru	um capricornutum)	
CAS: 6860	9-97-2 Oxirane, mo	no((C12-14-alkyloxy)methyl)derivatives	
EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)		
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)		
	1800 mg/l (Lepomis macrochirus)		
EC50	>100 mg/l (BEL)		
NOEC	500 mg/l (Pseudok	irchneriella subcapitata)	
CAS: 100-5	51-6 Benzyl alcoho		
IC50/72h	700 mg/l (algae)		
LC50/96h	460 mg/l (Pimephales promelas)		
	10 mg/l (Lepomis macrochirus)		
 12.2 Persis degradabil 12.3 Bioaco 	ity	No further relevant information available.	
potential		No further relevant information available.	
· 12.4 Mobili	ty in soil ts of PBT and vPvE	No further relevant information available.	
· PBT:		Not applicable.	
· vPvB:		Not applicable.	
	rine disrupting		
properties		For information on endocrine disrupting properties see section 11.	
	adverse effects ecological informa	tion:	
· General no		Do not allow product to reach ground water, water bodies or sewage system.	
		(Contd. on page 10)	

Page 9/13

(Contd. of page 8)

List II

List II



Page 10/13

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

allow product to reach sewage system.

Revision: 15.04.2025

Trade name MC-Estripox - Komponente A

(Contd. of page 9)

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

- **Recommendation** Must not be disposed of together with household garbage. Do not
- Uncleaned packagings:
- Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

• 14.1 UN number or ID number • ADR, IMDG, IATA	UN3082
• 14.2 UN proper shipping name • ADR, IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)
' IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin Solvent naphtha (petroleum), light, aromatic) MARINE POLLUTANT
· 14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances an articles.
Label	9
· IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
· Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
[.] 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
EMS Number:	F-A,S-F

_____GB



Page 11/13

GB

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

Trade name MC-Estripox - Komponente A

	(Contd. of page 10)
· Stowage Category	A
 14.7 Maritime transport in bulk account in bulk account in the second sec	rding to Not applicable.
· Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000
• Transport category • Tunnel restriction code	ml 3 (-)
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
• UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 Poisons Act
- · Regulated explosives precursors None of the ingredients is listed. · Regulated poisons None of the ingredients is listed. Reportable explosives precursors None of the ingredients is listed. Reportable poisons None of the ingredients is listed. · Directive 2012/18/EU · Qualifying quantity (tonnes) for the application of lower-200 t tier requirements • Qualifying quantity (tonnes) for the application of upper-500 t tier requirements (Contd. on page 12)



Page 12/13

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

(Contd. of page 11)

Trade name MC-Estripox - Komponente A

 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H360F May damage fertility. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract. Department issuing data specification sheet: Environment protection department. · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 1B: Reproductive toxicity - Category 1B



Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 36 (replaces version 35)

Revision: 15.04.2025

Page 13/13

Trade name MC-Estripox - Komponente A

(Contd. of page 12) STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• * Data compared to the previous version altered.