

MC-Additiv Retard

Fluid retarder for concrete cosmetic fillers



PRODUCT PROPERTIES

- Retarder for the adjustment of setting times for Emcefix-Spachtel/MC-Powertop and Nafuquick/MC-Quicktop concrete cosmetic fillers
- Highly concentrated, dilutable in water
- Chloride free
- Liquid
- No influence on concrete cosmetic colours

AREAS OF APPLICATION

- Retarding concrete cosmetic fillers

APPLICATION ADVICE

Description: MC-Additiv Retard retards the setting of mortars. The product is used in civil engineering and is also suitable as an additive for mortars used in concrete cosmetics.

Mixing: MC-Additiv Retard should be added to the mixing water. The degree of water dilution depends on the desired accelerating effect and should be determined in prior trial runs under the given conditions.

Example: Having a dilution factor of 1 : 7 (MC-Additiv Retard : water) at 20 °C, in this case the workability time of Emcefix and Nafuquick fillers is approx. 60 minutes.

Further Information: MC-Additiv Retard is highly acidic. Wear rubber gloves and protective goggles when working with the material.

The information on the safety data sheets must be observed.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	g/cm ³	1.02	
Mixing ratio (with water)	RT	1 : 7	
Application conditions	°C	≥ 5	
Self-monitoring	EN ISO 9001		
Storage	Can be stored in cool and dry conditions for at least 12 months in original unopened packs. Protect from frost.		
Colour	transparent		
Packaging disposal	Make sure single-use containers are completely empty.		

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018768]